1. Product Features

1.1 Electrical features

- V_{CES}=1200V
- $I_{C\ nom}$=75A / I_{CRM}=150A
- Low switching losses
- Low inductance
- Fast switching and short tail current
- Integrated NTC temperature sensor
- High power and thermal cycling capability



Figure1 IGBT Module

1.2 Mechanical features

- Integrated NTC temperature sensor
- High power and thermal cycling capability
- Al_2O_3 substrate with low thermal resistance

2. Typical Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- power supply

3. Description



Figure 2 SixPack

4. IGBT, Inverter

4.1 Maximum Rated Values

Parameter	Note or test condition	Symbol	Values	Unit
Collector-emitter voltage 集电极—发射极间电压	T_{vj} = 25°C	V_{CES}	1200	V
Continuous DC collector current 连续集电极电流	T_C = 87°C, $T_{vj, max}$ = 150°C	$I_{C\ nom}$	75	A
Repetitive peak collector current 集电极峰值电流	t_P = 1 ms	I_{CRM}	150	A
Total power dissipation 总功率损耗	T_C = 25°C, $T_{vj, max}$ = 175 °C	P_{tot}	357	W
Gate-emitter peak voltage 栅极－发射极峰值电压		V_{GES}	+/- 20	V

4.2 Characteristic value

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage 集电极－发射极饱和电压	I_C = 75 A, V_{GE} = 15 V	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	$V_{CE,sat}$		1.7 1.9 2.0		V V V
Gate threshold voltage 栅极阈值电压	I_C = 2.8mA, V_{CE} = V_{GE}, T_{vj} = 25°C		$V_{GE,th}$		5.9		V
Gate charge 栅极电荷	V_{GE} = -15 V ... +15 V		Q_G		0.8		µC
Internal gate resistor 内部栅极电阻	T_{vj} = 25°C		R_{Gint}		2.7		Ω
Input capacitance 输入电容	f=1MHz, T_{vj}=25°C, V_{CE}=25V, V_{GE}=0V		C_{ies}		9.8		nF
Reverse transfer capacitance 反向传输电容	f=1MHz, T_{vj}=25°C, V_{CE}=25V, V_{GE}=0V		C_{res}		0.1		nF
Collector-emitter cut-off current 集电极-发射极截止电流	V_{CE} = 1200 V, V_{GE} = 0 V, T_{vj} = 25°C		I_{CES}			1	mA
Gate-emitter leakage current 栅极-发射极漏电流	V_{CE} = 0 V, V_{GE} = 20 V, T_{vj} = 25°C		I_{GES}			100	nA
Turn-on delay time, inductive load 开通延迟时间	I_C = 75A, V_{CE} = 600V V_{GE} = +15/-15V $R_{G,on}$ = 4.1Ω	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	$t_{d,on}$		0.085 0.097 0.108		us us us
Rise time, inductive load 上升时间	I_C = 75A, V_{CE} = 600V V_{GE} = +15/-15V $R_{G,on}$ = 4.1Ω	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	t_r		0.032 0.036 0.038		us us us

(table continues...) 待续

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Turn-off delay time, inductive load 关断延迟时间	I_C = 50A, V_{CE} = 600V V_{GE} = +15/-15V $R_{G,off}$ = 6.8Ω	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	$t_{d,off}$		0.210 0.255 0.265		us us us
Fall time, inductive load 下降时间	I_C = 50A, V_{CE} = 600V V_{GE} = +15/-15V $R_{G,off}$ = 6.8Ω	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	t_f		0.250 0.333 0.416		us us us
Turn-on energy loss per pulse 开通损耗能量	I_C = 75A, V_{CE} = 600V, L_s=40nH V_{GE} = +15/-15V, di/dt =1580A/µs $R_{G,on}$ = 4.1Ω (T_{vj} = 150°C)	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	E_{on}		5.26 7.91 8.95		mJ mJ mJ
Turn-off energy loss per pulse 关断损耗能量	I_C = 75A, V_{CE} = 600V, L_s=40nH V_{GE} = +15/-15V, dv/dt =4640V/µs $R_{G,off}$ = 4.1Ω (T_{vj} = 150°C)	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	E_{off}		5.59 8.29 8.80		mJ mJ mJ
SC data 短路数据	V_{GE} ≤15V, V_{CC}=600 V, t_P ≤ 8 µs, T_{vj} = 150°C , C_{GE} = 0.0uF , V_{CEmax} = V_{CES} -L_{sCE} · di/dt		I_{SC}		440		A
Thermal resistance, junction to heatsink 结一外壳热阻	Per IGBT		$R_{th,JH}$			0.42	K/W

5. Diode, Inverter

5.1 Maximum Rated Values

Parameter	Note or test condition	Symbol	Values	Unit
Repetitive peak reverse voltage 反向重复峰值电压	T_{vj} = 25°C	V_{RRM}	1200	V
Continuous DC forward current 连续正向直流电流		I_F	75	A
Repetitive peak forward current 正向重复峰值电流	t_P = 1 ms	I_{FRM}	150	A

5.2 Characteristic value

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Forward voltage 正向电压	I_F = 50 A, V_{GE} = 0 V	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	V_F		1.8 1.9 1.9		V V V

(table continues...) 待续

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Peak reverse recovery current 反向恢复峰值电流	I_F = 75A, V_R = 600V V_{GE} = -15V , - di_F/dt = 2100 A/µs (T_{vj}=150°C)	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	I_{RM}		110 131 135		A A A
Recovered charge 恢复电荷	I_F = 75A, V_R = 600V V_{GE} = -15V , - di_F/dt = 2100 A/µs (T_{vj}=150°C)	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	Q_r		5.11 9.75 11.6		µC µC µC
Reverse recovery energy 反向恢复损耗（每脉冲）	I_F = 75A, V_R = 600V V_{GE} = -15V , - di_F/dt = 2100 A/µs (T_{vj}=150°C)	T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 150°C	E_{rec}		1.19 2.96 3.78		mJ mJ mJ
Thermal resistance, junction to heatsink 结－外壳热阻	Per diode		$R_{th,JH}$			0.43	K/W

6. NTC-Thermistor

6.1 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Rated resistance 额定电阻值	Tc = 25°C	R_{25}		5.00		KΩ
Power dissipation 耗散功耗	Tc = 25°C	P_{25}			20	mW
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298, 15K))]$	B_{25}/B_{50}		3400		K
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/75}(1/T_2-1/(298, 15K))]$	B_{25}/B_{75}		3430		K
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/100}(1/T_2-1/(298, 15K))]$	B_{25}/B_{100}		3445		K

(table continues...) 待续

7. Module

7.1 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Isolation Voltage 隔离电压	RMS, f=50HZ,1min	V_{ISOL}			2500	V
Stray inductance module 杂散电感		L_{sCE}		30		nH
Operation Junction Temperature 结温		T_{jop}	-40		150	˚C
Storage Temperature Range 存储温度范围		T_{stg}	-40		125	˚C
Mounting Torque 安装扭矩	Screw M4	M	2		2.3	N.m
Weight of Module 重量		G		42		g

8. Characteristics diagrams



Output characteristic IGBT, Inverter (typical)

$I_C = f(V_{CE})$, $V_{GE} = 15V$



Output characteristic IGBT, Inverter (typical)

$I_C = f(V_{CE})$, $T_{vj} = 150°C$



Transfer characteristic IGBT, Inverter (typical)

$I_C = f(V_{GE})$, $V_{CE} = 20V$



Switching losses IGBT, Inverter (typical)

$E_{on}=f(I_C)$, $E_{off} = f(I_C)$, $V_{GE} = \pm 15V$, $R_{Gon} = 4.1\ \Omega$
$R_{Goff} = 4.1\ \Omega$, $V_{CE} = 600V$



Switching losses IGBT, Inverter (typical)

$E_{on} = f(R_G)$, $E_{off} = f(R_G)$, $V_{GE} = \pm 15V$, $I_C = 75A$, $V_{CE} = 600V$



Transient thermal impedance IGBT, Inverter

$Z_{thJC} = f(t)$



Reverse bias safe operating area IGBT, Inverter (RBSOA)

$I_C = f(V_{CE})$ $V_{GE} = \pm 15V$, $R_{Goff} = 6.8\Omega$, Tvj = 150°C



Forward characteristic of Diode, Inverter (typical)

$I_F = f(V_F)$



Switching losses Diode, Inverter (typical)

$E_{rec} = f(I_F)$, $R_{Gon} = 4.1\ \Omega$, $V_{CE} = 600V$



Switching losses Diode, Inverter (typical)

$E_{rec} = f(R_G)$, $I_F = 75$ A, $V_{CE} = 600V$



Transient thermal impedance Diode Inverter

$Z_{thJC} = f(t)$



NTC-Thermistor-temperature characteristic (typical)

R=f(T)

9. Circuit Diagram



Figure 3

10. Package Outlines



Figure 4