

1. Product Features

1.1 Electrical features

- $V_{CES}=1200V$
- $I_{C\ nom}=200A / I_{CRM}=400A$
- Low switching losses
- Low inductance
- Fast switching and short tail current
- Integrated NTC temperature sensor
- High power and thermal cycling capability




Figure1 IGBT Module

1.2 Mechanical features

- Al_2O_3 substrate with low thermal resistance
- Copper base plate

2. Typical Applications

- Switching mode power supply
- Drive inverters
- Uninterruptible power supply
- AC and DC servo drive amplifier

3. Description




Figure 2 SixPack

4. IGBT, Inverter

4.1 Maximum rated values

Parameter	Note or test condition	Symbol	Values	Unit
Collector-emitter voltage 集电极—发射极间电压	$T_{vj} = 25^{\circ}\text{C}$	V_{CES}	1200	V
Continuous DC collector current 连续集电极电流	$T_C = 72^{\circ}\text{C}, T_{vj\ max} = 150^{\circ}\text{C}$	$I_{C\ nom}$	200	A
Repetitive peak collector current 集电极峰值电流	$t_P = 1\ ms$	I_{CRM}	400	A
Total power dissipation 总功率损耗	$T_C = 25^{\circ}\text{C}, T_{vj\ max} = 175^{\circ}\text{C}$	P_{tot}	750	W
Gate-emitter peak voltage 栅极—发射极峰值电压		V_{GES}	+/- 20	V

4.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter saturation voltage 集电极—发射极饱和电压	$I_C = 200\ \text{A}, V_{GE} = 15\ \text{V}$	$T_{vj} = 25^{\circ}\text{C}$		1.59		V
		$T_{vj} = 125^{\circ}\text{C}$		1.86		V
		$T_{vj} = 150^{\circ}\text{C}$		1.94		V
Gate threshold voltage 栅极阈值电压	$I_C = 6\ \text{mA}, V_{CE} = V_{GE}, T_{vj} = 25^{\circ}\text{C}$	$V_{GE,th}$	5.0	5.8	6.5	V
Gate charge 栅极电荷	$V_{GE} = -15\ \text{V} \dots +15\ \text{V}$	Q_G		1.90		μC
Internal gate resistor 内部栅极电阻	$T_{vj} = 25^{\circ}\text{C}$	R_{Gint}		1.70		Ω
Input capacitance 输入电容	$f=1\ \text{MHz}, T_{vj}=25^{\circ}\text{C}, V_{CE}=25\ \text{V}, V_{GE}=0\ \text{V}$	C_{ies}		33.4		nF
Reverse transfer capacitance 反向传输电容	$f=1\ \text{MHz}, T_{vj}=25^{\circ}\text{C}, V_{CE}=25\ \text{V}, V_{GE}=0\ \text{V}$	C_{res}		0.17		nF
Collector-emitter cut-off current 集电极-发射极截止电流	$V_{CE} = 1200\ \text{V}, V_{GE} = 0\ \text{V}, T_{vj} = 25^{\circ}\text{C}$	I_{CES}			1	mA
Gate-emitter leakage current 栅极-发射极漏电流	$V_{CE} = 0\ \text{V}, V_{GE} = 20\ \text{V}, T_{vj} = 25^{\circ}\text{C}$	I_{GES}			100	nA
Turn-on delay time, inductive load 开通延迟时间	$I_C = 200\ \text{A}, V_{CE} = 600\ \text{V}$ $V_{GE} = +15/-15\ \text{V}$ $R_{G,on} = 5\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$		0.17		us
		$T_{vj} = 125^{\circ}\text{C}$		0.22		us
		$T_{vj} = 150^{\circ}\text{C}$		0.22		us
Rise time, inductive load 上升时间	$I_C = 200\ \text{A}, V_{CE} = 600\ \text{V}$ $V_{GE} = +15/-15\ \text{V}$ $R_{G,on} = 5\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$		0.06		us
		$T_{vj} = 125^{\circ}\text{C}$		0.08		us
		$T_{vj} = 150^{\circ}\text{C}$		0.09		us

(table continues...) 待续

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Turn-off delay time, inductive load 关断延迟时间	$I_C = 200A, V_{CE} = 600V$ $V_{GE} = +15/-15V$ $R_{G,off} = 5\Omega$	$T_{vj} = 25^\circ C$	$t_{d,off}$		0.31		us
		$T_{vj} = 125^\circ C$			0.41		us
		$T_{vj} = 150^\circ C$			0.42		us
Fall time, inductive load 下降时间	$I_C = 200A, V_{CE} = 600V$ $V_{GE} = +15/-15V$ $R_{G,off} = 5\Omega$	$T_{vj} = 25^\circ C$	t_f		0.21		us
		$T_{vj} = 125^\circ C$			0.28		us
		$T_{vj} = 150^\circ C$			0.35		us
Turn-on energy loss per pulse 开通损耗能量	$I_C = 200A, V_{CE} = 600V, L_s = 30nH$ $V_{GE} = +15/-15V, di/dt = 1300A/\mu s$ $R_{G,on} = 5\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$	E_{on}		14.6		mJ
		$T_{vj} = 125^\circ C$			31.4		mJ
		$T_{vj} = 150^\circ C$			36.3		mJ
Turn-off energy loss per pulse 关断损耗能量	$I_C = 200A, V_{CE} = 600V, L_s = 30nH$ $V_{GE} = +15/-15V, dv/dt = 5900V/\mu s$ $R_{G,off} = 5\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$	E_{off}		11.0		mJ
		$T_{vj} = 125^\circ C$			17.2		mJ
		$T_{vj} = 150^\circ C$			18.8		mJ
SC data 短路数据	$V_{GE} \leq 15V, V_{CC} = 600V, t_P \leq 8\mu s, T_{vj} = 150^\circ C,$ $C_{GE} = 0.0\mu F, V_{CEmax} = V_{CES} - L_{SCE} \cdot di/dt$		I_{sc}		1407		A
Thermal resistance, junction to case 结-外壳热阻	Per IGBT		$R_{th,Jc}$			0.20	K/W

5. Diode

5.1 Maximum rated values

Parameter	Note or test condition	Symbol	Values	Unit
Repetitive peak reverse voltage 反向重复峰值电压	$T_{vj} = 25^\circ C$	V_{RRM}	1200	V
Continuous DC forward current 连续正向直流电流		I_F	200	A
Repetitive peak forward current 正向重复峰值电流	$t_P = 1\text{ ms}$	I_{FRM}	400	A

5.2 Characteristic value

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Forward voltage 正向电压	$I_F = 200\text{ A}, V_{GE} = 0\text{ V}$	$T_{vj} = 25^\circ C$	V_F		1.69		V
		$T_{vj} = 125^\circ C$			1.41		V
		$T_{vj} = 150^\circ C$			1.34		V

(table continues...) 待续

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Peak reverse recovery current 反向恢复峰值电流	I _F = 200A, V _R = 600V V _{GE} = -15V, - di _F /dt = 2320 A/μs (T _{vj} =150°C)	T _{vj} = 25°C	I _{RM}		215		A
		T _{vj} = 125°C			261		A
		T _{vj} = 150°C			285		A
Recovered charge 恢复电荷	I _F = 200A, V _R = 600V V _{GE} = -15V, - di _F /dt = 2320 A/μs (T _{vj} =150°C)	T _{vj} = 25°C	Q _r		22.7		μC
		T _{vj} = 125°C			52.1		μC
		T _{vj} = 150°C			64.4		μC
Reverse recovery energy 反向恢复损耗 (每脉冲)	I _F = 200A, V _R = 600V V _{GE} = -15V, - di _F /dt = 2320 A/μs (T _{vj} =150°C)	T _{vj} = 25°C	E _{rec}		4.96		mJ
		T _{vj} = 125°C			13.9		mJ
		T _{vj} = 150°C			18.4		mJ
Thermal resistance, junction to case 结—外壳热阻	Per diode		R _{th,jc}			0.25	K/W

6. NTC-Thermistor

6.1 Characteristic value


Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Rated resistance 额定电阻值	T _c = 25°C	R ₂₅		5.00		KΩ
Power dissipation 耗散功耗	T _c = 25°C	P ₂₅			20	mW
B-value B-Z 值	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298, 15K))]$	B ₂₅ /B ₅₀		3375		K
B-value B-Z 值	$R_2 = R_{25} \exp[B_{25/75}(1/T_2 - 1/(298, 15K))]$	B ₂₅ /B ₇₅		3408		K
B-value B-Z 值	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298, 15K))]$	B ₂₅ /B ₁₀₀		3436		K



7. Module

7.1 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Isolation Voltage 隔离电压	RMS, f=50HZ,1min	V _{ISOL}			2500	V
Stray inductance module 杂散电感		L _{sCE}		30		nH
Operation Junction Temperature 结温		T _{jop}	-40		150	°C
Storage Temperature Range 存储温度范围		T _{stg}	-40		125	°C
Mounting Torque 安装扭矩	Screw M5	M	3		6	N.m
Weight of Module 重量		G		300		g

8. Characteristics diagrams







Switching losses IGBT (typical)

$E_{on} = f(R_G), E_{off} = f(R_G)$

$I_C = 200\text{ A}, V_{CE} = 600\text{ V}, V_{GE} = \pm 15\text{ V}$

Transient thermal impedance IGBT

$Z_{thjc} = f(t)$




Reverse bias safe operating area IGBT (RBSOA)

$I_C = f(V_{CE})$


$V_{GE} = 15\text{ V}, R_{Goff} = 5\ \Omega, T_{vj} = 150\ \text{°C}$

Forward characteristic of Diode (typical)


$I_F = f(V_F)$




Switching losses Diode (typical)
 $E_{rec} = f(I_F)$
 $R_{Gon} = 5 \Omega, V_{CE} = 600 V$



Switching losses Diode (typical)
 $E_{rec} = f(R_G)$
 $I_F = 200 A, V_{CE} = 600 V$



Transient thermal impedance Diode
 $Z_{thjc} = f(t)$



NTC-Thermistor-temperature characteristic (typical)
 $R = f(T_{NTC})$

9. Circuit Diagram




Figure 3

10. Package Outlines




Figure 4