

## 1. Product Features

### 1.1 Electrical features

- $V_{CES}=1200V$
- $I_{C\ nom}=50A / I_{CRM}=100A$
- Low switching losses
- Low inductance
- Fast switching and short tail current
- Integrated NTC temperature sensor
- High power and thermal cycling capability



Figure1 IGBT Module

### 1.2 Mechanical features

- $Al_2O_3$  substrate with low thermal resistance
- Copper base plate

## 2. Typical Applications

- Switching mode power supply
- Drive inverters with brake system
- Uninterruptible power supply
- AC and DC servo drive amplifier

## 3. Description




Figure 2 3 Phase Bridge+Brake

## 4. IGBT, Inverter

### 4.1 Maximum Rated Values

Parameter	Note or test condition	Symbol	Values	Unit
Collector-emitter voltage 集电极—发射极间电压	$T_{vj} = 25^{\circ}\text{C}$	$V_{CES}$	1200	V
Continuous DC collector current 连续集电极电流	$T_c = 100^{\circ}\text{C}, T_{vj} \text{ max} = 150^{\circ}\text{C}$	$I_{C \text{ nom}}$	50	A
Repetitive peak collector current 集电极峰值电流	$t_P = 1 \text{ ms}$	$I_{CRM}$	100	A
Total power dissipation 总功率损耗	$T_c = 25^{\circ}\text{C}, T_{vj} \text{ max} = 150^{\circ}\text{C}$	$P_{\text{tot}}$	210	W
Gate-emitter peak voltage 栅极—发射极峰值电压		$V_{GES}$	+/- 20	V

### 4.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter saturation voltage 集电极—发射极饱和电压	$I_C = 50 \text{ A}, V_{GE} = 15 \text{ V}$	$V_{CE, \text{sat}}$	1.5	$T_{vj} = 25^{\circ}\text{C}$ 1.7	1.9	V
				$T_{vj} = 125^{\circ}\text{C}$ 2.0		V
				$T_{vj} = 150^{\circ}\text{C}$ 2.1		V
Gate threshold voltage 栅极阈值电压	$I_C = 1 \text{ mA}, V_{CE} = V_{GE}, T_{vj} = 25^{\circ}\text{C}$	$V_{GE, \text{th}}$	5.0	5.6	6.5	V
Gate charge 栅极电荷	$V_{GE} = -15 \text{ V} \dots +15 \text{ V}$	$Q_G$		0.44		$\mu\text{C}$
Internal gate resistor 内部栅极电阻	$T_{vj} = 25^{\circ}\text{C}$	$R_{G \text{ int}}$		2.2		$\Omega$
Input capacitance 输入电容	$f = 1 \text{ MHz}, T_{vj} = 25^{\circ}\text{C}, V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}$	$C_{\text{ies}}$		6.15		nF
Reverse transfer capacitance 反向传输电容	$f = 1 \text{ MHz}, T_{vj} = 25^{\circ}\text{C}, V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}$	$C_{\text{res}}$		0.08		nF
Collector-emitter cut-off current 集电极-发射极截止电流	$V_{CE} = 1200 \text{ V}, V_{GE} = 0 \text{ V}, T_{vj} = 25^{\circ}\text{C}$	$I_{CES}$			1	mA
Gate-emitter leakage current 栅极-发射极漏电流	$V_{CE} = 0 \text{ V}, V_{GE} = 20 \text{ V}, T_{vj} = 25^{\circ}\text{C}$	$I_{GES}$			100	nA
Turn-on delay time, inductive load 开通延迟时间	$I_C = 50 \text{ A}, V_{CE} = 600 \text{ V}$ $V_{GE} = +15/-15 \text{ V}$ $R_{G, \text{on}} = 15 \Omega$	$t_{d, \text{on}}$		$T_{vj} = 25^{\circ}\text{C}$ 0.13		$\mu\text{s}$
				$T_{vj} = 125^{\circ}\text{C}$ 0.14		$\mu\text{s}$
				$T_{vj} = 150^{\circ}\text{C}$ 0.14		$\mu\text{s}$
Rise time, inductive load 上升时间	$I_C = 50 \text{ A}, V_{CE} = 600 \text{ V}$ $V_{GE} = +15/-15 \text{ V}$ $R_{G, \text{on}} = 15 \Omega$	$t_r$		$T_{vj} = 25^{\circ}\text{C}$ 0.06		$\mu\text{s}$
				$T_{vj} = 125^{\circ}\text{C}$ 0.07		$\mu\text{s}$
				$T_{vj} = 150^{\circ}\text{C}$ 0.07		$\mu\text{s}$

(table continues...) 待续

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Turn-off delay time, inductive load 关断延迟时间	$I_C = 50A, V_{CE} = 600V$ $V_{GE} = +15/-15V$ $R_{G,off} = 15\Omega$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	$t_{d,off}$		0.24	us
					0.27	us
					0.28	us
Fall time, inductive load 下降时间	$I_C = 50A, V_{CE} = 600V$ $V_{GE} = +15/-15V$ $R_{G,off} = 5\Omega$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	$t_f$		0.28	us
					0.46	us
					0.48	us
Turn-on energy loss per pulse 开通损耗能量	$I_C = 50A, V_{CE} = 600V, L_s = 35nH$ $V_{GE} = +15/-15V, di/dt = 580A/\mu s$ $R_{G,on} = 15\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	$E_{on}$		6.83	mJ
					9.00	mJ
					9.78	mJ
Turn-off energy loss per pulse 关断损耗能量	$I_C = 50A, V_{CE} = 600V, L_s = 35nH$ $V_{GE} = +15/-15V, dv/dt = 4700V/\mu s$ $R_{G,off} = 15\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	$E_{off}$		3.37	mJ
					4.86	mJ
					5.28	mJ
SC data 短路数据	$V_{GE} \leq 15V, V_{CC} = 600V, t_P \leq 8\mu s, T_{vj} = 150^\circ C,$ $C_{GE} = 0.0\mu F, V_{CEmax} = V_{CES} - L_{SCE} \cdot di/dt$	$I_{sc}$		340		A
Thermal resistance, junction to case 结-外壳热阻	Per IGBT	$R_{th,jc}$			0.50	K/W

## 5. Diode, Inverter

### 5.1 Maximum Rated Values

Parameter	Note or test condition	Symbol	Values	Unit
Repetitive peak reverse voltage 反向重复峰值电压	$T_{vj} = 25^\circ C$	$V_{RRM}$	1200	V
Continuous DC forward current 连续正向直流电流		$I_F$	50	A
Repetitive peak forward current 正向重复峰值电流	$t_P = 1ms$	$I_{FRM}$	100	A

### 5.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage 正向电压	$I_F = 50A, V_{GE} = 0V$	$V_F$		1.79	V	
				1.80	V	
				1.74	V	

(table continues...) 待续

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Peak reverse recovery current 反向恢复峰值电流	$I_F = 50A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 480 A/\mu s$ $(T_{vj}=150^\circ C)$	$I_{RM}$		$T_{vj} = 25^\circ C$	59	A
				$T_{vj} = 125^\circ C$	68	A
				$T_{vj} = 150^\circ C$	71	A
Recovered charge 恢复电荷	$I_F = 50A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 480 A/\mu s$ $(T_{vj}=150^\circ C)$	$Q_F$		$T_{vj} = 25^\circ C$	3.6	$\mu C$
				$T_{vj} = 125^\circ C$	6.3	$\mu C$
				$T_{vj} = 150^\circ C$	7.4	$\mu C$
Reverse recovery energy 反向恢复损耗 (每脉冲)	$I_F = 50A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 480 A/\mu s$ $(T_{vj}=150^\circ C)$	$E_{rec}$		$T_{vj} = 25^\circ C$	0.5	mJ
				$T_{vj} = 125^\circ C$	1.2	mJ
				$T_{vj} = 150^\circ C$	1.6	mJ
Thermal resistance, junction to case 结—外壳热阻	Per diode	$R_{th,Jc}$			0.54	K/W

## 6. Diode, Rectifier

### 6.1 Maximum Rated Values

Parameter	Note or test condition	Symbol	Values	Unit
Repetitive peak reverse voltage 反向重复峰值电压	$T_{vj} = 25^\circ C$	$V_{RRM}$	1600	V
Average Rectified Output current 整流器输出均方根电流	$V_F = 1.2, T_{vj} = 150^\circ C$	$I_F$	50	A
Surge forward current 正向浪涌电流	$t_p = 10 ms, T_{vj} = 150^\circ C$	$I_{FSM}$	320	A
$I^2t$ - value $I^2t$ -值	$t_p = 10 ms, T_{vj} = 150^\circ C$	$I^2t$	510	A <sup>2</sup> s

### 6.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage 正向电压	$T_{vj} = 150^\circ C, I_F = 50 A$	$V_F$		1.1		V
Reverse current 反向电流	$T_{vj} = 150^\circ C, V_R = 1600 V$	$I_R$		1		mA
Thermal resistance, junction to case 结—外壳热阻	Per diode	$R_{th,Jc}$			0.75	K/W

## 7. NTC-Thermistor

### 7.1 Characteristic value


Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Rated resistance 额定电阻值	T <sub>c</sub> = 25°C	R <sub>25</sub>		5.00		KΩ
Power dissipation 耗散功耗	T <sub>c</sub> = 25°C	P <sub>25</sub>			240	mW
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298, 15K))]$	B <sub>25</sub> /B <sub>50</sub>		3400		K
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/75}(1/T_2-1/(298, 15K))]$	B <sub>25</sub> /B <sub>75</sub>		3430		K
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/100}(1/T_2-1/(298, 15K))]$	B <sub>25</sub> /B <sub>100</sub>		3445		K



## 8. Module

### 8.1 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Isolation Voltage 隔离电压	RMS, f=50HZ,1min	V <sub>ISOL</sub>			2500	V
Stray inductance module 杂散电感		L <sub>sCE</sub>		35		nH
Operation Junction Temperature 结温		T <sub>jop</sub>	-40		150	°C
Storage Temperature Range 存储温度范围		T <sub>stg</sub>	-40		125	°C
Mounting Torque 安装扭矩	Screw M5	M	3		6	N.m
Weight of Module 重量		G		180		g



## 9. Characteristics diagrams









**Switching losses IGBT, Inverter (typical)**  
 $E_{on} = f(R_G)$ ,  $E_{off} = f(R_G)$   $V_{GE} = \pm 15\text{V}$ ,  $I_c = 50\text{A}$ ,  $V_{CE} = 600\text{V}$


**Transient thermal impedance IGBT, Inverter**  
 $Z_{thjC} = f(t)$



**Reverse bias safe operating area IGBT, Inverter (RBSOA)**  
 $I_c = f(V_{CE})$   $V_{GE} = \pm 15\text{V}$   $R_{Goff} = 15\Omega$ ,  $T_{vj} = 150^\circ\text{C}$

**Forward characteristic of Diode, Inverter (typical)**  
 $I_F = f(V_F)$

	
<p><b>Switching losses Diode, Inverter (typical)</b>  <math>E_{rec} = f(I_F)</math> <math>R_{Gon} = 15\Omega</math>, <math>V_{CE} = 600V</math></p>	<p><b>Switching losses Diode, Inverter (typical)</b>  <math>E_{rec} = f(R_G)</math> <math>I_F = 50A</math>, <math>V_{CE} = 600V</math></p>
	
<p><b>Transient thermal impedance Diode Inverter</b>  <math>Z_{thjC} = f(t)</math></p>	<p><b>Forward characteristic of Diode, Rectifier (typical)</b>  <math>I_F = f(V_F)</math></p>

	
<p><b>NTC-Thermistor-temperature characteristic (typical)</b>  <math>R=f(T)</math></p>	

### 10. Circuit Diagram




Figure 3

### 11. Package Outlines




Figure 4

Technical datasheet