

1. Product Features

1.1 Electrical features

- $V_{CES}=1200V$
- $I_{C\ nom}=75A / I_{CRM}=150A$
- Low switching losses
- Low inductance
- Fast switching and short tail current
- Integrated NTC temperature sensor
- High power and thermal cycling capability




Figure 1 IGBT Module

1.2 Mechanical features

- Al_2O_3 substrate with low thermal resistance
- Copper base plate

2. Typical Applications

- Switching mode power supply
- Drive inverters
- Uninterruptible power supply
- AC and DC servo drive amplifier

3. Description




Figure 2 3 Phase Bridge+ Rectifier

4. IGBT, Inverter

4.1 Maximum rated values

Parameter	Note or test condition	Symbol	Values	Unit
Collector-emitter voltage 集电极—发射极间电压	$T_{vj} = 25^{\circ}\text{C}$	V_{CES}	1200	V
Continuous DC collector current 连续集电极电流	$T_C = 100^{\circ}\text{C}, T_{vj\ max} = 150^{\circ}\text{C}$	$I_{C\ nom}$	75	A
Repetitive peak collector current 集电极峰值电流	$t_P = 1\ \text{ms}$	I_{CRM}	150	A
Total power dissipation 总功率损耗	$T_C = 25^{\circ}\text{C}, T_{vj\ max} = 175^{\circ}\text{C}$	P_{tot}	395	W
Gate-emitter peak voltage 栅极—发射极峰值电压		V_{GES}	+/- 20	V

4.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter saturation voltage 集电极—发射极饱和电压	$I_C = 75\ \text{A}, V_{GE} = 15\ \text{V}$	$T_{vj} = 25^{\circ}\text{C}$		1.54		V
		$T_{vj} = 125^{\circ}\text{C}$		1.65		V
		$T_{vj} = 150^{\circ}\text{C}$		1.70		V
Gate threshold voltage 栅极阈值电压	$I_C = 1.5\ \text{mA}, V_{CE} = V_{GE}, T_{vj} = 25^{\circ}\text{C}$	$V_{GE,th}$	5.0	6.0	6.5	V
Gate charge 栅极电荷	$V_{GE} = -15\ \text{V} \dots +15\ \text{V}$	Q_G		0.81		μC
Internal gate resistor 内部栅极电阻	$T_{vj} = 25^{\circ}\text{C}$	R_{Gint}		2.70		Ω
Input capacitance 输入电容	$f=1\ \text{MHz}, T_{vj}=25^{\circ}\text{C}, V_{CE}=25\ \text{V}, V_{GE}=0\ \text{V}$	C_{ies}		9.80		nF
Reverse transfer capacitance 反向传输电容	$f=1\ \text{MHz}, T_{vj}=25^{\circ}\text{C}, V_{CE}=25\ \text{V}, V_{GE}=0\ \text{V}$	C_{res}		0.12		nF
Collector-emitter cut-off current 集电极-发射极截止电流	$V_{CE} = 1200\ \text{V}, V_{GE} = 0\ \text{V}, T_{vj} = 25^{\circ}\text{C}$	I_{CES}			1	mA
Gate-emitter leakage current 栅极-发射极漏电流	$V_{CE} = 0\ \text{V}, V_{GE} = 20\ \text{V}, T_{vj} = 25^{\circ}\text{C}$	I_{GES}			100	nA
Turn-on delay time, inductive load 开通延迟时间	$I_C = 75\ \text{A}, V_{CE} = 600\ \text{V}$ $V_{GE} = +15/-15\ \text{V}$ $R_{G,on} = 5\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$		0.17		us
		$T_{vj} = 125^{\circ}\text{C}$		0.18		us
		$T_{vj} = 150^{\circ}\text{C}$		0.18		us
Rise time, inductive load 上升时间	$I_C = 75\ \text{A}, V_{CE} = 600\ \text{V}$ $V_{GE} = +15/-15\ \text{V}$ $R_{G,on} = 5\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$		0.05		us
		$T_{vj} = 125^{\circ}\text{C}$		0.06		us
		$T_{vj} = 150^{\circ}\text{C}$		0.07		us

(table continues...) 待续

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Turn-off delay time, inductive load 关断延迟时间	$I_C = 75A, V_{CE} = 600V$ $V_{GE} = +15/-15V$ $R_{G,off} = 5\Omega$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	$t_{d,off}$		0.23	us
					0.27	
					0.27	
Fall time, inductive load 下降时间	$I_C = 75A, V_{CE} = 600V$ $V_{GE} = +15/-15V$ $R_{G,off} = 5\Omega$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	t_f		0.25	us
					0.26	
					0.32	
Turn-on energy loss per pulse 开通损耗能量	$I_C = 75A, V_{CE} = 600V, L_s = 30nH$ $V_{GE} = +15/-15V, di/dt = 1470A/\mu s$ $R_{G,on} = 5\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	E_{on}		5.36	mJ
					7.36	
					8.14	
Turn-off energy loss per pulse 关断损耗能量	$I_C = 75A, V_{CE} = 600V, L_s = 30nH$ $V_{GE} = +15/-15V, dv/dt = 4190V/\mu s$ $R_{G,off} = 5\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	E_{off}		4.39	mJ
					5.65	
					6.83	
SC data 短路数据	$V_{GE} \leq 15V, V_{CC} = 600V, t_p \leq 8\mu s, T_{vj} = 150^\circ C,$ $C_{GE} = 0.0\mu F, V_{CEmax} = V_{CES} - L_{SCE} \cdot di/dt$	I_{sc}		548		A
Thermal resistance, junction to case 结-外壳热阻	Per IGBT	$R_{th,jc}$			0.38	K/W

5. Diode, Inverter

5.1 Maximum rated values

Parameter	Note or test condition	Symbol	Values	Unit
Repetitive peak reverse voltage 反向重复峰值电压	$T_{vj} = 25^\circ C$	V_{RRM}	1200	V
Continuous DC forward current 连续正向直流电流		I_F	75	A
Repetitive peak forward current 正向重复峰值电流	$t_p = 1\text{ ms}$	I_{FRM}	150	A

5.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage 正向电压	$I_F = 75\text{ A}, V_{GE} = 0\text{ V}$	V_F		1.66	V	
				1.67		
				1.62		

(table continues...) 待续

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Peak reverse recovery current 反向恢复峰值电流	$I_F = 75A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 1176 A/\mu s$ $R_{G,off} = 5\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	I_{RM}		51.4	A
					81.0	A
					83.5	A
Recovered charge 恢复电荷	$I_F = 75A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 1176 A/\mu s$ $R_{G,off} = 5\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	Q_r		3.57	μC
					7.89	μC
					9.28	μC
Reverse recovery energy 反向恢复损耗 (每脉冲)	$I_F = 75A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 1176 A/\mu s$ $R_{G,off} = 5\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	E_{rec}		0.49	mJ
					1.10	mJ
					1.77	mJ
Thermal resistance, junction to case 结-外壳热阻	Per diode	$R_{th,JC}$			0.45	K/W

6. Diode, Rectifier

6.1 Maximum rated values

Parameter	Note or test condition	Symbol	Values	Unit
Repetitive peak reverse voltage 反向重复峰值电压	$T_{vj} = 25^\circ C$	V_{RRM}	1600	V
Average Rectified Output current 整流器输出均方根电流	$V_F = 1.2, T_{vj} = 150^\circ C$	I_F	75	A
Surge forward current 正向浪涌电流	$t_p = 10 ms, T_{vj} = 150^\circ C$	I_{FSM}	515	A
I^2t - value I^2t -值	$t_p = 10 ms, T_{vj} = 150^\circ C$	I^2t	1330	A^2s

6.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage 正向电压	$T_{vj} = 150^\circ C, I_F = 75 A$	V_F		1.10		V
Reverse current 反向电流	$T_{vj} = 150^\circ C, V_R = 1600 V$	I_R		1.00		mA
Thermal resistance, junction to case 结-外壳热阻	Per diode	$R_{th,JC}$			0.43	K/W

7. NTC-Thermistor

7.1 Characteristic value


Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Rated resistance 额定电阻值	T _c = 25°C	R ₂₅		5.00		KΩ
Power dissipation 耗散功耗	T _c = 25°C	P ₂₅			20	mW
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298, 15K))]$	B ₂₅ /B ₅₀		3400		K
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/75}(1/T_2-1/(298, 15K))]$	B ₂₅ /B ₇₅		3430		K
B-value B-Z 值	$R_2=R_{25}\exp[B_{25/100}(1/T_2-1/(298, 15K))]$	B ₂₅ /B ₁₀₀		3445		K



8. Module

8.1 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Isolation Voltage 隔离电压	RMS, f=50HZ,1min	V _{ISOL}			2500	V
Stray inductance module 杂散电感		L _{SCE}		40		nH
Operation Junction Temperature 结温		T _{jop}	-40		150	°C
Storage Temperature Range 存储温度范围		T _{stg}	-40		125	°C
Mounting Torque 安装扭矩	Screw M5	M	3		6	N.m
Weight of Module 重量		G		300		g

9. Characteristics diagrams






Switching losses IGBT, Inverter (typical)

$E_{on} = f(R_G)$, $E_{off} = f(R_G)$
 $I_C = 75$ A, $V_{CE} = 600$ V, $V_{GE} = \pm 15$ V


Transient thermal impedance IGBT, Inverter

$Z_{thjC} = f(t)$




Reverse bias safe operating area IGBT, Inverter (RBSOA)

$I_C = f(V_{CE})$
 $V_{GE} = 15$ V, $R_{Goff} = 5$ Ω , $T_{vj} = 150$ $^\circ C$




Forward characteristic of Diode, Inverter (typical)


$I_F = f(V_F)$




Switching losses Diode, Inverter (typical)
 $E_{rec} = f(I_F)$
 $R_{Gon} = 5 \Omega, V_{CE} = 600 \text{ V}$



Switching losses Diode, Inverter (typical)
 $E_{rec} = f(R_G)$
 $I_F = 75 \text{ A}, V_{CE} = 600 \text{ V}$



Transient thermal impedance Diode, Inverter
 $Z_{thjC} = f(t)$



Forward characteristic of Diode, Rectifier (typical)
 $I_F = f(V_f)$

