

1. Product Features

1.1 Electrical features

- $V_{CES}=1200V$
- $I_{C\ nom}=300A / I_{CRM}=600A$
- Low switching losses
- Low inductance
- Fast switching and short tail current
- High power and thermal cycling capability



Figure1 IGBT Module

1.2 Mechanical features

- High power and thermal cycling capability
- Al_2O_3 substrate with low thermal resistance
- Copper base plate

2. Typical Applications

- Switching mode power supply
- Drive inverters with brake system
- Uninterruptible power supply
- AC and DC servo drive amplifier

3. Description




Figure 2 Half Bridge

4. IGBT, Inverter

4.1 Maximum Rated Values

Parameter	Note or test condition	Symbol	Values	Unit
Collector-emitter voltage 集电极—发射极间电压	$T_{vj} = 25^{\circ}\text{C}$	V_{CES}	1200	V
Continuous DC collector current 连续集电极电流	$T_C = 100^{\circ}\text{C}, T_{vj, \max} = 150^{\circ}\text{C}$	$I_{C \text{ nom}}$	300	A
Repetitive peak collector current 集电极峰值电流	$t_P = 1 \text{ ms}$	I_{CRM}	600	A
Total power dissipation 总功率损耗	$T_C = 25^{\circ}\text{C}, T_{vj, \max} = 175^{\circ}\text{C}$	P_{tot}	1070	W
Gate-emitter peak voltage 栅极—发射极峰值电压		V_{GES}	+/- 20	V

4.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit	
			Min.	Typ.	Max.		
Collector-emitter saturation voltage 集电极—发射极饱和电压	$I_C = 300 \text{ A}, V_{GE} = 15 \text{ V}$	$V_{CE, \text{sat}}$		$T_{vj} = 25^{\circ}\text{C}$	1.45	1.90	V
				$T_{vj} = 125^{\circ}\text{C}$	1.60		V
				$T_{vj} = 150^{\circ}\text{C}$	1.65		V
Gate threshold voltage 栅极阈值电压	$I_C = 11.4 \text{ mA}, V_{CE} = V_{GE}, T_{vj} = 25^{\circ}\text{C}$	$V_{GE, \text{th}}$	5.0	5.8	6.5	V	
Gate charge 栅极电荷	$V_{GE} = -15 \text{ V} \dots +15 \text{ V}$	Q_G		3.45		μC	
Internal gate resistor 内部栅极电阻	$T_{vj} = 25^{\circ}\text{C}$	$R_{G \text{ int}}$		1.05		Ω	
Input capacitance 输入电容	$f = 1 \text{ MHz}, T_{vj} = 25^{\circ}\text{C}, V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}$	C_{ies}		43		nF	
Reverse transfer capacitance 反向传输电容	$f = 1 \text{ MHz}, T_{vj} = 25^{\circ}\text{C}, V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}$	C_{res}		0.3		nF	
Collector-emitter cut-off current 集电极-发射极截止电流	$V_{CE} = 1200 \text{ V}, V_{GE} = 0 \text{ V}, T_{vj} = 25^{\circ}\text{C}$	I_{CES}			2	mA	
Gate-emitter leakage current 栅极-发射极漏电流	$V_{CE} = 0 \text{ V}, V_{GE} = 20 \text{ V}, T_{vj} = 25^{\circ}\text{C}$	I_{GES}			200	nA	
Turn-on delay time, inductive load 开通延迟时间	$I_C = 300 \text{ A}, V_{CE} = 600 \text{ V}$ $V_{GE} = +15/-15 \text{ V}$ $R_{G, \text{on}} = 3.3 \Omega$	$t_{d, \text{on}}$		$T_{vj} = 25^{\circ}\text{C}$	0.20		us
				$T_{vj} = 125^{\circ}\text{C}$	0.23		us
				$T_{vj} = 150^{\circ}\text{C}$	0.23		us
Rise time, inductive load 上升时间	$I_C = 300 \text{ A}, V_{CE} = 600 \text{ V}$ $V_{GE} = +15/-15 \text{ V}$ $R_{G, \text{on}} = 3.3 \Omega$	t_r		$T_{vj} = 25^{\circ}\text{C}$	0.07		us
				$T_{vj} = 125^{\circ}\text{C}$	0.09		us
				$T_{vj} = 150^{\circ}\text{C}$	0.09		us

(table continues...) 待续

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Turn-off delay time, inductive load 关断延迟时间	$I_C = 300A, V_{CE} = 600V$ $V_{GE} = +15/-15V$ $R_{G,off} = 3.3\Omega$	$T_{vj} = 25^\circ C$	$t_{d,off}$		0.48		us
		$T_{vj} = 125^\circ C$			0.54		us
		$T_{vj} = 150^\circ C$			0.55		us
Fall time, inductive load 下降时间	$I_C = 300A, V_{CE} = 600V$ $V_{GE} = +15/-15V$ $R_{G,off} = 3.3\Omega$	$T_{vj} = 25^\circ C$	t_f		0.25		us
		$T_{vj} = 125^\circ C$			0.39		us
		$T_{vj} = 150^\circ C$			0.41		us
Turn-on energy loss per pulse 开通损耗能量	$I_C = 300A, V_{CE} = 600V, L_s=20nH$ $V_{GE} = +15/-15V, di/dt = 2600A/\mu s$ $R_{G,on} = 3.3\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$	E_{on}		27.4		mJ
		$T_{vj} = 125^\circ C$			48.6		mJ
		$T_{vj} = 150^\circ C$			55.8		mJ
Turn-off energy loss per pulse 关断损耗能量	$I_C = 300A, V_{CE} = 600V, L_s=20nH$ $V_{GE} = +15/-15V, dv/dt = 3550V/\mu s$ $R_{G,off} = 3.3\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$	E_{off}		27.7		mJ
		$T_{vj} = 125^\circ C$			37.0		mJ
		$T_{vj} = 150^\circ C$			39.8		mJ
SC data 短路数据	$V_{GE} \leq 15V, V_{CC}=600V, t_p \leq 8\mu s, T_{vj} = 150^\circ C,$ $C_{GE} = 0.0\mu F, V_{CEmax} = V_{CES} - L_{sCE} \cdot di/dt$		I_{SC}		1400		A
Thermal resistance, junction to case 结-外壳热阻	Per IGBT		$R_{th,JC}$			0.12	K/W

5. Diode, Inverter

5.1 Maximum Rated Values

Parameter	Note or test condition	Symbol	Values	Unit
Repetitive peak reverse voltage 反向重复峰值电压	$T_{vj} = 25^\circ C$	V_{RRM}	1200	V
Continuous DC forward current 连续正向直流电流		I_F	300	A
Repetitive peak forward current 正向重复峰值电流	$t_P = 1ms$	I_{FRM}	600	A

5.2 Characteristic value

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Forward voltage 正向电压	$I_F = 300A, V_{GE} = 0V$	$T_{vj} = 25^\circ C$	V_F		2.00	2.40	V
		$T_{vj} = 125^\circ C$			1.65		V
		$T_{vj} = 150^\circ C$			1.60		V

(table continues...) 待续

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Peak reverse recovery current 反向恢复峰值电流	$I_F = 300A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 1150 A/\mu s$ ($T_{vj}=150^\circ C$)	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	I_{RM}		210 300 320		A A A
Recovered charge 恢复电荷	$I_F = 300A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 1150 A/\mu s$ ($T_{vj}=150^\circ C$)	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	Q_r		20 50 61		μC μC μC
Reverse recovery energy 反向恢复损耗 (每脉冲)	$I_F = 300A, V_R = 600V$ $V_{GE} = -15V, -di_F/dt = 1150 A/\mu s$ ($T_{vj}=150^\circ C$)	$T_{vj} = 25^\circ C$ $T_{vj} = 125^\circ C$ $T_{vj} = 150^\circ C$	E_{rec}		4.0 11.5 14.7		mJ mJ mJ
Thermal resistance, junction to case 结—外壳热阻	Per diode		$R_{th,jc}$			0.2	K/W

6. Module


6.1 Characteristic value





Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Isolation Voltage 隔离电压	RMS, f=50HZ,1min	V_{ISOL}			2500	V
Stray inductance module 杂散电感		L_{SCE}		20		nH




(table continues...) 待续

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Operation Junction Temperature 结温		T_{jop}	-40		150	$^\circ C$
Storage Temperature Range 存储温度范围		T_{stg}	-40		125	$^\circ C$
Mounting Torque 安装扭矩	Screw M6	M	3		6	N.m
Terminal Connection Torque 端子连接扭矩	Screw M6	M	2.5		5	N.m
Weight of Module 重量		G		340		g

7. Characteristics diagrams



	
<p>Switching losses IGBT, Inverter (typical) $E_{on} = f(R_G)$, $E_{off} = f(R_G)$ $V_{GE} = \pm 15V$, $I_C = 300A$, $V_{CE} = 600V$</p>	<p>Transient thermal impedance IGBT, Inverter $Z_{thJC} = f(t)$</p>
	
<p>Reverse bias safe operating area IGBT, Inverter (RBSOA) $I_C = f(V_{CE})$ $V_{GE} = \pm 15V$ $R_{Goff} = 3.3 \Omega$, $T_{vj} = 150^\circ C$</p>	<p>Forward characteristic of Diode, Inverter (typical) $I_F = f(V_F)$</p>

	
<p>Switching losses Diode, Inverter (typical) $E_{rec} = f(I_F) R_{Gon} = 3.3 \Omega, V_{CC} = 600V$</p>	<p>Switching losses Diode, Inverter (typical) $E_{rec} = f(R_G) I_F = 300 A, V_{CC} = 600V$</p>
	
<p>ransient thermal impedance Diode Inverter $Z_{th,jc} = f(t)$</p>	

8. Circuit Diagram




Figure 3

9. Package Outlines




Figure 4