

## 1. Product Features

### 1.1 Electrical features

- $V_{CES}=1700V$
- $I_{C\ nom}=1400A / I_{CRM}=2800A$
- Low switching losses
- Low  $V_{cesat}$
- High DC Stability
- High current density
- Integrated NTC temperature sensor




Figure 1

### 1.2 Mechanical features

- Al<sub>2</sub>O<sub>3</sub> substrate with low thermal resistance
- Copper base plate
- Package with CTI > 400
- High power and thermal cycling capability

## 2. Typical Applications

- 3-Level Applications
- Auxiliary Inverters
- High power converters
- Motor Drives
- Wind Turbines

## 3. Description




Figure 2 Half Bridge

## 4. IGBT

### 4.1 Maximum rated values

Parameter	Note or test condition	Symbol	Values	Unit
Collector-emitter voltage 集电极—发射极间电压	$T_{vj} = 25^{\circ}\text{C}$	$V_{CES}$	1700	V
Continuous DC collector current 连续集电极电流	$T_C = 104^{\circ}\text{C}, T_{vj\ max} = 150^{\circ}\text{C}$	$I_{C\ nom}$	1400	A
Repetitive peak collector current 集电极峰值电流	$t_P = 1\ \text{ms}$	$I_{CRM}$	2800	A
Total power dissipation 总功率损耗	$T_C = 25^{\circ}\text{C}, T_{vj\ max} = 175^{\circ}\text{C}$	$P_{tot}$	9.26	KW
Gate-emitter peak voltage 栅极—发射极峰值电压		$V_{GES}$	+/- 20	V

### 4.2 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter saturation voltage 集电极—发射极饱和电压	$I_C = 1400\ \text{A}, V_{GE} = 15\ \text{V}$	$T_{vj} = 25^{\circ}\text{C}$		1.65		V
		$T_{vj} = 125^{\circ}\text{C}$		1.96		V
		$T_{vj} = 150^{\circ}\text{C}$		2.00		V
Gate threshold voltage 栅极阈值电压	$I_C = 8\ \text{mA}, V_{CE} = V_{GE}, T_{vj} = 25^{\circ}\text{C}$	$V_{GE,th}$	5.0	5.6	6.2	V
Gate charge 栅极电荷	$V_{GE} = -15\ \text{V} \dots +15\ \text{V}$	$Q_G$		1.90		$\mu\text{C}$
Internal gate resistor 内部栅极电阻	$T_{vj} = 25^{\circ}\text{C}$	$R_{Gint}$		0.45		$\Omega$
Input capacitance 输入电容	$f=1\ \text{MHz}, T_{vj}=25^{\circ}\text{C}, V_{CE}=25\ \text{V}, V_{GE}=0\ \text{V}$	$C_{ies}$		183		nF
Reverse transfer capacitance 反向传输电容	$f=1\ \text{MHz}, T_{vj}=25^{\circ}\text{C}, V_{CE}=25\ \text{V}, V_{GE}=0\ \text{V}$	$C_{res}$		7.73		nF
Collector-emitter cut-off current 集电极-发射极截止电流	$V_{CE} = 1700\ \text{V}, V_{GE} = 0\ \text{V}, T_{vj} = 25^{\circ}\text{C}$	$I_{CES}$			10	mA
Gate-emitter leakage current 栅极-发射极漏电流	$V_{CE} = 0\ \text{V}, V_{GE} = 20\ \text{V}, T_{vj} = 25^{\circ}\text{C}$	$I_{GES}$			1	$\mu\text{A}$
Turn-on delay time, inductive load 开通延迟时间	$I_C = 1400\ \text{A}, V_{CE} = 900\ \text{V}$ $V_{GE} = +15/-15\ \text{V}$ $R_{G,on} = 1.6\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$		0.51		$\mu\text{s}$
		$T_{vj} = 125^{\circ}\text{C}$		0.52		$\mu\text{s}$
		$T_{vj} = 150^{\circ}\text{C}$		0.53		$\mu\text{s}$
Rise time, inductive load 上升时间	$I_C = 1400\ \text{A}, V_{CE} = 900\ \text{V}$ $V_{GE} = +15/-15\ \text{V}$ $R_{G,on} = 1.6\ \Omega$	$T_{vj} = 25^{\circ}\text{C}$		0.14		$\mu\text{s}$
		$T_{vj} = 125^{\circ}\text{C}$		0.16		$\mu\text{s}$
		$T_{vj} = 150^{\circ}\text{C}$		0.17		$\mu\text{s}$

(table continues...) 待续

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Turn-off delay time, inductive load 关断延迟时间	$I_C = 1400A, V_{CE} = 900V$ $V_{GE} = +15/-15V$ $R_{G,off} = 1.6\Omega$	$T_{vj} = 25^\circ C$	$t_{d,off}$		1.01		us
		$T_{vj} = 125^\circ C$			1.08		us
		$T_{vj} = 150^\circ C$			1.11		us
Fall time, inductive load 下降时间	$I_C = 1400A, V_{CE} = 900V$ $V_{GE} = +15/-15V$ $R_{G,off} = 1.6\Omega$	$T_{vj} = 25^\circ C$	$t_f$		0.23		us
		$T_{vj} = 125^\circ C$			0.41		us
		$T_{vj} = 150^\circ C$			0.47		us
Turn-on energy loss per pulse 开通损耗能量	$I_C = 1400A, V_{CE} = 900V, L_s = 30nH$ $V_{GE} = +15/-15V, di/dt = 6600A/\mu s$ $R_{G,on} = 1.6\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$	$E_{on}$		161		mJ
		$T_{vj} = 125^\circ C$			220		mJ
		$T_{vj} = 150^\circ C$			242		mJ
Turn-off energy loss per pulse 关断损耗能量	$I_C = 1400A, V_{CE} = 900V, L_s = 30nH$ $V_{GE} = +15/-15V, dv/dt = 3930V/\mu s$ $R_{G,off} = 1.6\Omega (T_{vj} = 150^\circ C)$	$T_{vj} = 25^\circ C$	$E_{off}$		314		mJ
		$T_{vj} = 125^\circ C$			410		mJ
		$T_{vj} = 150^\circ C$			440		mJ
SC data 短路数据	$V_{GE} \leq 15V, V_{CC} = 1000V, t_p \leq 8\mu s, T_{vj} = 150^\circ C,$ $C_{GE} = 0.0\mu F, V_{CEmax} = V_{CES} - L_{SCE} \cdot di/dt$		$I_{sc}$		9600		A
Thermal resistance, junction to case 结-外壳热阻	Per IGBT		$R_{th,Jc}$			16.2	K/KW

## 5. Diode

### 5.1 Maximum rated values

Parameter	Note or test condition	Symbol	Values	Unit
Repetitive peak reverse voltage 反向重复峰值电压	$T_{vj} = 25^\circ C$	$V_{RRM}$	1700	V
Continuous DC forward current 连续正向直流电流		$I_F$	1400	A
Repetitive peak forward current 正向重复峰值电流	$t_p = 1ms$	$I_{FRM}$	2800	A

### 5.2 Characteristic value

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Forward voltage 正向电压	$I_F = 1400A, V_{GE} = 0V$	$T_{vj} = 25^\circ C$	$V_F$		1.92		V
		$T_{vj} = 125^\circ C$			2.07		V
		$T_{vj} = 150^\circ C$			2.09		V

(table continues...) 待续

Parameter	Note or test condition		Symbol	Values			Unit
				Min.	Typ.	Max.	
Peak reverse recovery current 反向恢复峰值电流	$I_F = 1400A, V_R = 900V$ $V_{GE} = -15V, -di_F/dt = 7910 A/\mu s$ ( $T_{vj}=150^\circ C$ )	$T_{vj} = 25^\circ C$	$I_{RM}$		1306		A
		$T_{vj} = 125^\circ C$			1327		A
		$T_{vj} = 150^\circ C$			1342		A
Recovered charge 恢复电荷	$I_F = 1400A, V_R = 900V$ $V_{GE} = -15V, -di_F/dt = 7910 A/\mu s$ ( $T_{vj}=150^\circ C$ )	$T_{vj} = 25^\circ C$	$Q_r$		291		$\mu C$
		$T_{vj} = 125^\circ C$			397		$\mu C$
		$T_{vj} = 150^\circ C$			434		$\mu C$
Reverse recovery energy 反向恢复损耗 (每脉冲)	$I_F = 1400A, V_R = 900V$ $V_{GE} = -15V, -di_F/dt = 7910 A/\mu s$ ( $T_{vj}=150^\circ C$ )	$T_{vj} = 25^\circ C$	$E_{rec}$		171		mJ
		$T_{vj} = 125^\circ C$			235		mJ
		$T_{vj} = 150^\circ C$			256		mJ
Thermal resistance, junction to case 结—外壳热阻	Per diode		$R_{th,Jc}$			33.7	K/KW

## 6. NTC-Thermistor

### 6.1 Characteristic value


Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Rated resistance 额定电阻值	$T_c = 25^\circ C$	$R_{25}$		5.00		K $\Omega$
Power dissipation 耗散功耗	$T_c = 25^\circ C$	$P_{25}$			20	mW
B-value B-Z 值	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298, 15K))]$	$B_{25}/B_{50}$		3375		K
B-value B-Z 值	$R_2 = R_{25} \exp[B_{25/75}(1/T_2 - 1/(298, 15K))]$	$B_{25}/B_{75}$		3408		K
B-value B-Z 值	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298, 15K))]$	$B_{25}/B_{100}$		3436		K



## 7. Module

### 7.1 Characteristic value

Parameter	Note or test condition	Symbol	Values			Unit
			Min.	Typ.	Max.	
Isolation Voltage 隔离电压	RMS, f=50HZ,1min	V <sub>ISOL</sub>			4000	V
Stray inductance module 杂散电感		L <sub>sCE</sub>		10		nH
Operation Junction Temperature 结温		T <sub>jop</sub>	-40		150	°C
Storage Temperature Range 存储温度范围		T <sub>stg</sub>	-40		125	°C
Mounting Torque 安装扭矩	Screw M5	M	3.0		6.0	N.m
Terminal Connection Torque 端子扭矩 I	Screw M4	M	1.8		2.1	N.m
Terminal Connection Torque 端子扭矩 II	Screw M8	M	8.0		10	N.m
Weight of Module 重量		G		1200		g



## 8. Characteristics diagrams






**Switching losses IGBT (typical)**  
 $E_{on} = f(R_G)$ ,  $E_{off} = f(R_G)$   
 $I_C = 1400\text{ A}$ ,  $V_{CE} = 900\text{ V}$ ,  $V_{GE} = \pm 15\text{ V}$

**Transient thermal impedance IGBT**  
 $Z_{thjC} = f(t)$




**Reverse bias safe operating area IGBT (RBSOA)**  
 $I_C = f(V_{CE})$   
 $V_{GE} = 15\text{ V}$ ,  $R_{Goff} = 1.6\ \Omega$ ,  $T_{vj} = 150\text{ }^\circ\text{C}$


**Forward characteristic of Diode (typical)**  
 $I_F = f(V_F)$




**Switching losses Diode (typical)**  
 $E_{rec} = f(I_F)$   
 $R_{Gon} = 1.6 \Omega, V_{CE} = 900 \text{ V}$



**Switching losses Diode (typical)**  
 $E_{rec} = f(R_G)$   
 $I_F = 1400 \text{ A}, V_{CE} = 900 \text{ V}$



**Transient thermal impedance Diode**  
 $Z_{thJC} = f(t)$



**NTC-Thermistor-temperature characteristic (typical)**  
 $R = f(T_{NTC})$

### 9. Circuit Diagram




Figure 3

### 10. Package Outlines




Figure 4